

# BlueLOG M



Bluetooth temperature and tilt data logger, managed through Android and iOS devices with BlueTrails App for Transport monitoring. The data logger is paired to a Smartphone and transmits data via Bluetooth (BLE 5.0 but works with 4.0 and above also) at a programmable rate. Data are displayed in real time on the Smartphone screen and alarms occur when temperature is out of limits. Upon delivery it is possible to send data via email. Connecting a Bluetooth thermal printer data can be printed to be given with delivery documents.

In the front it has a contactless tag to be immediately associated with your Smartphone. You can also pair it by reading the QR Code or by pressing a button.

With anti repositioning function, to be activated using its [wall mount](#).



## Main features

- Internal temperature sensor
- Buzzer for acoustic alarms
- Tilt monitoring
- Pairing with the phone via QR Code, button and Contactless Tag (on the back of the logger)
- Anti tamper function
- Extended memory
- Internal antenna
- Different monitoring modes: in real time (even multiple loggers at the same time) or with unloading at destination
- Start and Stop via push button
- Locate your logger among many by turning on the LEDs or activating the Buzzer
- Long battery life: 2 years with continuous transmission every 15 minutes
- Real time check against user programmable alarm thresholds
- Visual and acoustic alarms
- Generates PDF, excel, csv reports that can be sent via email
- **Optional reference traceable calibration certificate available**
- Possibility to send data to Tecnosoft **Cloud**, Nebula of Data (NOD)

## Plus

- No extra accessory: your Smartphone is all you need
- Small size suitable for every package and box
- Real time alarms
- Bluetooth printer paired to the smartphone available
- BLE 5.0 for long range and quick transmission: **transmits thousands of data in few seconds!**

## The system

BlueLOG data logger does not need of any additional accessory. Just download the Android App and you are ready to start using it.

## Accessories

- Bluetooth printer
- BlueLOG/TempNFC/TempBLE wall mount

## Applications



Cold Chain



Logistic & Transport



Environment



Pharmaceutical



Food & Beverages



Healthcare



Medical



Laboratories

## Technical specifications

Dimensions	67 X 20 X 97 (mm)
Weight	18 g
Temperature range	-30 °C ÷ +60 °C
Standard calibration points (temperature)	-30/0/20/60°C
Extra calibration points (temperature)	Within standard calibration range
Temperature resolution	0,01 °C
Temperature accuracy	± 0.5 °C without certificate / ± 0,2 °C with Accredia traceable certificate (valid in the calibration range)
Memory (n. of acquisitions)	8.730
Buttons and functions	Immediate reading, start, pairing buttons
Acquisition step	From 1 minute up (in steps of 1 minute)
Functions	Tilt monitoring, anti tamper function, buzzer for acoustic alarms
Alarms	Local (acoustic and/or visual)
Communication	Bluetooth BLE 5.0
Battery life	Up to 2 years life with acquisition rate of 15 minutes
Battery type	2 X AA 1,5 V batteries
Protection degree	IP66
Software&Mobile App	BlueTrails
It requires	Bluetooth 4.0 device or above
Accessories	Bluetooth Printer