

DiskInterface HS



DiskInterface HS (High Speed) is the connection bay used for downloading data and programming all models of high temperature data loggers, included the bluetooth devices BlueWave, models for pressure (PressureDisk) and humidity (RHTemp). There are also the DiskInterface HS Mini (all models of SterilDisk, il PasteurDisk Can and lo SterilDisk Can, P-Micro, S-Micro) or Universal Multibay (all models). It allows the communication between the data loggers and its management programs, SPD, HumiPressureDisk, TS Manager. Devices that can be connected are:

- BlueWave (all versions)
- SterilDisk (all versions)
- PasteurDisk Can
- SterilDisk Can
- P-Micro (all versions)
- S-Micro (all versions)
- S-Disk J (all versions)
- S-MicroW (all versions)
- P- Radio (all versions)
- S-Radio (all versions)
- PressureDisk (all versions)
- RHTemp (all versions)
- L-Disk (all versions)



Main features

- Easy to use
- Status LED
- Shows battery status on software when logger is connected

Accessories

- TS Manager 3
- SPD
- HumiPressureDisk
- TS Manager
- Tecno Calib

Technical specifications

Materials	ABS, Rubber, Stainless Steel
Communication	USB
Cable	Included
Data loggers supported	SterilDisk, P-Micro, S-Micro, S-Disk J, MicroW, L-Disk, RHTemp, PressureDisk, S-Radio, Pirani vacuum Logger,
Software&Mobile App	TS Manager 3, SPD, HumipressureDisk, TS Manager, Tecno Calib

